



## Samson Elegant Matt

Samson Elegant Matt is an excellent quality soft matt acrylic paint for interior, exterior walls, and ceilings.

Colours: White

### PRODUCT USES

- Long lasting matt wall paint for interior and exterior walls and ceilings.
- Suitable for use on new and previously painted primed plaster, cement, fibre-cement, and brickwork.
- Suitable for high wear areas such as passages, bedrooms, living rooms, offices, and commercial areas.

### ADVANTAGES

- Elegant, long lasting, smooth matt finish.
- Stain resistant.
- Washable with good scrubbability.
- High obliteration with excellent recoating properties.
- Covers minor imperfections and repairs fine cracks.
- Water-based and easy to apply.
- Low odour, lead, and heavy metal free.
- 8-year quality guarantee.

### THEORETICAL SPREADRATE

- 8-10m<sup>2</sup> per litre per coat. Applied in a 2-coat application.
- This is a guide only and depends on substrate porosity and profile as well as technique and tools used.

### SURFACE PREPARATION

- Ensure all surfaces are sound and properly cleaned and free of any contaminants such as dirt, algae, rust and salt.
- Surfaces must be completely dry with no more than 10% moisture content.
- Repair any cracks in the surface.
  
- For new brick walls, plaster, and concrete - after suitable surface preparation, prime with a coat of **Samson Plaster Primer** according to instructions and allow to dry.
  
- For previously painted surfaces – remove fungal growth and loose and flaking paint with a wire brush or high-pressure cleaner. Apply a coat of **Samson FungiVanish** if necessary. Prime powdery surfaces with **Samson Bonding Liquid**. Glossy paints should be sanded well prior to application.

## APPLICATION

- Stir Samson Elegant Matt thoroughly with a flat paddle before use.
- Samson Elegant Matt is ready to use, no need to dilute.
- Suggested order of painting starts with ceilings, then walls and then finish with doors, windows, and trims.
- Apply paint evenly with long smooth strokes using a brush, roller, or airless spray.
- Apply two coats to achieve complete obliteration.
- For external applications left to dry overnight, rinse the surface with clean water and leave to dry before applying second or third coat.
- Application Environment:
  - Surface temperature: min 10°C - max 35°C
  - Ambient temperature: min 10°C - max 35°C
  - Relative humidity: min 10% - max 85%
- For colour consistency ensure batch numbers are the same on all containers that you purchase.

## CLEANING

- Hands and equipment are easily cleaned in water while wet.
- Collect spills with suitable absorbent material

## IMPORTANT

- Do not apply if rain is expected.
- Ambient and surface temperatures must be between 10°C and 35°C during application.

## SAFETY PRECAUTIONS

- Skin contact: Wash thoroughly with soap and water.
- Eye contact: Flush immediately with water and contact a physician.
- Respiratory problems: Remove affected person to fresh air immediately and contact a physician.
- Not for consumption. If swallowed, contact a doctor immediately. Do not induce vomiting. Drink water.
- Keep out of reach of children.

## TECHNICAL DATA

- Pack size 5L and 20L buckets
- Touch dry 1 hour
- Recoating time 4 hours
- Toxicity Non-Toxic
- Fire hazard None
- Shelf life 6-12 months (dependent on storage conditions)
- Storage Cool, dry area below 25°C

Properties listed above are for guidance only and not a guarantee on performance.

## GUARANTEE

Samson Products (Pty) Ltd offers an 8 year guarantee on the Samson Elegant Matt. To register your guarantee, call the Samson Products offices on 031 7198840 within 30 days of purchase, and supply your contact details, the site details, purchase details, batch number and related products used. You will receive a guarantee reference number that you will need to record and keep with purchase slip for future reference. For terms and conditions please visit [www.samsonpaints.co.za](http://www.samsonpaints.co.za)

Technical details above are provided in good faith. Our paint range is manufactured by an ISO 9001: 2015 registered company and so our products are manufactured to the highest standards using raw materials of superior quality. Consequently we believe in the quality of our products and will willingly replace any product in the unlikely event of a quality related performance failure. Whilst we are confident in guaranteeing the quality of our products, we cannot however accept any liability for performance failure due to the incorrect application of our products. Correct application is critical to the successful performance of our products and as this process falls outside of our control we are unable to cover the application under our product performance warranty. Where there are doubts, it is recommended that the user conduct their own suitability tests before use.

Updated: November 2021 (this supersedes all previous publications)