



Roof Coat

Samson Roof Coat is a superior pure acrylic roof paint that offers long lasting protection for your roof. It's all round weather and UV resistance together with its unique anti fungicide ensures effective protection against fading and chalking. With a 10 year guarantee Samson Roof Coat is the best choice for an excellent finish on all roof types.

Colours: Black, Charcoal, Grey, Rustic Red, Terracotta, Brown, Court Green and White

PRODUCT USES

- Cement Roof Tiles
- Fibre Cement Roofs
- Galvanized iron roofs (for best results use Samson Metal Primer prior to using Samson Roof Coat)
- Window Sills and Fascias
- Galvanized iron garage doors, gutters and down pipes

ADVANTAGES

- UV and weather resistant
- Protection against fading and chalking
- Mold and Algae resistance.
- Water based – easy application and clean up
- Attractive range of colours
- Non-Toxic, Lead and heavy metal free.
- Superior quality with 10 year guarantee

COVERAGE

- 6 - 8m² per litre per coat.
- This is a guide only and depends on substrate porosity and profile as well as technique and tools used.

SURFACE PREPARATION

- Ensure all surfaces are properly cleaned using strong brush or high pressure cleaner. Allow to dry thoroughly.
- Remove grease, other contaminants as well as loose flaking paint and surface oxidation.
- Remove mildew stains and fungi with Samson FungiVanish.
- **New surfaces:**
 - New cement and Fibre cement roof tiles – Apply one coat suitable Bonding Liquid then 2 coats Samson Roof Coat.
 - New Galvanized Roofs – Wash with suitable galvanized cleaner as per instructions. Rinse well and allow to dry. Prime with Samson Metal Primer. Within 48 hours apply two coats Samson Roof Coat.
- **Previously painted surfaces:**
 - Weathered cement and Fibre cement roofs – Clean thoroughly, seal loose and powdery surfaces with suitable bonding liquid as per instructions, apply two coats Samson Roof Coat.
 - Galvanized Roofs – Clean and prepare surface prior to painting, wash down with Samson FungiVanish, remove heavy, loose and flaking rust with wire brush, wash well with water and allow to dry. Prime with Samson Metal Primer, allow to dry. Apply two coats Samson Roof Coat.

APPLICATION

- Stir Samson Roof Coat thoroughly before use.
- Apply using roller, brush or airless spray.
- Allow 4-6 hours @ 25°C drying time between coats. Drying times may vary with temperature and humidity.
- For colour consistency ensure batch numbers are the same on all containers that you purchase.

CLEANING

- Hands and equipment are easily cleaned in water while wet.
- Collect spills with suitable absorbent material

IMPORTANT

- Do not apply if rain is expected.
- Samson Roof Coat is not suitable for use on slate
- Ambient and surface temperatures must be between 10°C and 35°C during application.

SAFETY PRECAUTIONS

- Skin contact: Wash thoroughly with soap and water.
- Eye contact: Flush immediately with water and contact a physician.
- Respiratory problems: Remove affected person to fresh air immediately and contact a physician.
- Not for consumption. If swallowed, contact a doctor immediately. Do not induce vomiting. Drink water.
- Keep out of reach of children.

TECHNICAL DATA

- Pack size 5 litre and 20litre buckets
- Touch dry 2 hours
- Hard dry 4 hours
- Second coating time 6 hours
- Volume solids ±30%
- Viscosity 95-105 Ku
- Application temperature 20°C to 40°C
- Flexibility & weathering Excellent
- UV & Abrasion Resistance Excellent
- Density 1.12 – 1.18 g/l depending on the colour.
- Toxicity Non Toxic
- Fire hazard None
- Shelf life 6-12 months (dependent on storage conditions)
- Storage Cool, dry area below 25°C

Properties listed above are for guidance only and not a guarantee on performance.

GUARANTEE

Samson Products (Pty) Ltd offers a 10 year guarantee on the Samson Roof Coat. To register your guarantee, call the Samson Products offices on 031 7198840 within 30 days of purchase, and supply your contact details, the site details, purchase details, batch number and related products used. You will receive a guarantee reference number that you will need to record and keep with purchase slip for future reference. For terms and conditions please visit www.samsonpaints.co.za

Technical details above are provided in good faith. Samson Paints are manufactured by an ISO 9001: 2015 registered company and so our products are manufactured to the highest standards using raw materials of superior quality. Consequently we believe in the quality of our products and will willingly replace any product in the unlikely event of a quality related performance failure. Whilst we are confident in guaranteeing the quality of our products, we cannot however accept any liability for performance failure due to the incorrect application of our products. Correct application is critical to the successful performance of our products and as this process falls outside of our control we are unable to cover the application under our product performance warranty. Where there are doubts, it is recommended that the user conduct their own suitability tests before use.

Updated: February 2019 (this supersedes all previous publications)