



Ultra Sheen

Samson Ultra Sheen is a premium quality luxurious medium sheen paint suitable for both interior and exterior application. Virtually odor free with superior stain and wear resistance it is guaranteed to transform your home with lasting luxury.

Colours: White

Tint Bases: Pastel, Transparent and Deep

PRODUCT USES

- Interior and Exterior walls
- Suitably primed new and previously painter plaster, concrete, wood and various building boards

ADVANTAGES

- Matt sheen finish
- Exceptional durability
- Stain and dirt resistance
- Mold and Algae resistance.
- Water based – easy application and clean up

COVERAGE

- 6 - 8m² / litre per coat at 50 µm DFT. This is a theoretical spread rate only.
- Practical spread rate depends on substrate porosity and profile as well as technique and tools used.

SURFACE PREPARATION

- Ensure all surfaces are dry, sound and free from dust, dirt, grease and other contaminants as well as loose flaking paint and surface oxidation.
- Remove any mildew stains and fungi with Samson FungiVanish.
- **New surfaces:**
 - *New cement and Fibre cement* – Ensure concrete dried for at least 4 weeks before painting. Remove loose particles, oil, grease and mould, rinse and dry thoroughly. Apply Samson Plaster Primer as per instructions and allow to dry. For Fibre cement apply one coat of Samson SB29 bonding liquid and allow to dry prior to application of Samson Plaster Primer.
 - *Gypsum plaster* – Apply one coat Samson Plaster.
 - *Wood* – Sand smooth with 150 grit paper working in the direction of the wood grain. Dust off, seal knots and resinous areas with a knot seal product. Prime exterior of wood with a wood primer.
- **Previously painted surfaces:**
 - *Surfaces in good condition* – remove loose flaky paint by scrapng and sanding, spot prime bare areas with suitable primer. Clean surface with sugar soap and rinse with clean water. Sand glossy surfaces to a matt finish. Seal chalky surfaces with Samson SB29 or Samson Plaster Primer
 - *Surfaces in poor condition* – completely remove paint by most appropriate means. Treat as for new surface. Fill defects with polyfilla, seal filed areas with Samson Plaster Primer.

APPLICATION

- Stir Samson Ultra Sheen thoroughly before use. Apply using roller, brush or airless spray.
- Apply two or three coats to correctly primed surfaces to achieve complete obliteration.
- Allow 2-4 hours @ 25°C drying time between coats. Drying times may vary with temperature and humidity.
- For colour consistency ensure batch numbers are the same on all containers that you purchase.
- When applying tinted colours to new masonry surfaces, first prime with Samson Plaster Primer.

CLEANING

- Hands and equipment are easily cleaned in water while wet.
- Collect spills with suitable absorbent material

IMPORTANT

- Do not apply if rain is expected.
- Ambient and surface temperatures must be between 10°C and 35°C during application.

SAFETY PRECAUTIONS

- Skin contact: Wash thoroughly with soap and water.
- Eye contact: Flush immediately with water and contact a physician.
- Respiratory problems: Remove affected person to fresh air immediately and contact a physician.
- Not for consumption. If swallowed, contact a doctor immediately. Do not induce vomiting. Drink water.
- Keep out of reach of children.

TECHNICAL DATA

- Pack size 5L and 20L buckets
- Touch dry 1 hours
- Dry to handle 2 hours
- Recoating time 2 hours
- Application temperature 20°C to 40°C
- Viscosity 95-110 Ku
- Volume solids - White 32%
 - Pastel Base 40%
 - Deep Base 38%
 - Transparent Base 30%
- Density - White 1.28 kg/l
 - Pastel Base 1.01kg/l
 - Deep Base 1.01kg/l
 - Transparent Base 1.18kg/l
- Toxicity Non Toxic
- Shelf life 6-12 months (dependent on storage conditions)
- Storage Cool, dry area below 25°C

Properties listed above are for guidance only and not a guarantee on performance.

TINT BASES

- Tint base containers are under filled to levels which are specific for that base to allow for a calculated volume of colourants to be added. Volume indicated on container is only achieved after addition of prescribed colourants as per formulation.
- Tint bases are unfinished intermediate products which are not intended for use by themselves. A finished product is only achieved once prescribed quantities of colourants have been thoroughly mixed with tint base.
- When mixed to a finished product it's technical features, product information, application and surface preparation details comply with that of Samson Super Acrylic.

GUARANTEE

Samson Products offers a 10 year guarantee on the Samson Ultra Sheen. To register your guarantee, call the Samson Product offices on 031 7198840 within 30 days of purchase, and supply your contact details, the site details, purchase details, batch number and related products used. You will receive a guarantee reference number that you will need to record and keep with purchase slip for future reference. For terms and conditions please visit www.samsonpaints.co.za

Technical details above are provided in good faith. Samson paints is manufactured by an ISO 9001: 2015 registered company and our products are manufactured to the highest standards using raw materials of superior quality. Consequently we believe in the quality of our products and will willingly replace any product in the unlikely event of a quality related performance failure. Whilst we are confident in guaranteeing the quality of our products, we cannot however accept any liability for performance failure due to the incorrect application of our products. Correct application is critical to the successful performance of our products and as this process falls outside of our control we are unable to cover the application under our product performance warranty. Where there are doubts, it is recommended that the user conduct their own suitability tests before use.

Updated: February 2019 (this supersedes all previous publications)